

Background Check: A general technique to build more reliable and versatile classifiers

Miquel Perello-Nieto^{*1}, Telmo M. Silva Filho^{*2}, Meelis Kull¹ and Peter Flach¹

* Equal contribution

¹Department of Computer Science, University of Bristol, UK

²Centro de Informatica, Universidade Federal de Pernambuco, Brazil

Email: ¹{Miquel.PerelloNieto, Meelis.Kull, Peter.Flach}@bristol.ac.uk, ²tmsf@cin.ufpe.br

December 13, 2016


Representing uncertainty

1. Cautious classification
2. Outlier detection
3. Classification with confidence

Representing uncertainty

1. Cautious classification
2. Outlier detection
3. Classification with confidence


	$p(C_1 x)$	$p(C_2 x)$
A		
B		
C		
D		
E		



Representing uncertainty

1. Cautious classification
2. Outlier detection
3. Classification with confidence


	$p(C_1 x)$	$p(C_2 x)$
A	1	.0
B	.5	.5
C	.0	1
D	.5	.5
E	.5	.5



Representing uncertainty

1. Cautious classification
2. Outlier detection
3. Classification with confidence


	$p(C_1 x)$	$p(C_2 x)$	$p(b x)$
A	1	.0	
B	.5	.5	
C	.0	1	
D	.5	.5	
E	.5	.5	



Representing uncertainty


1. Cautious classification
2. Outlier detection
3. Classification with confidence

	$p(C_1 x)$	$p(C_2 x)$	$p(b x)$
A	1 → .9	.0 → .0	.1
B	.5 → .5	.5 → .5	.0
C	.0 → .0	1 → .5	.5
D	.5 → .0	.5 → .0	1
E	.5 → .1	.5 → .1	.8





Performing Background Check

- *Discriminative* approach
 - ▶ Pre-trained classifier
 - ▶ Generate background
 - ▶ Train binary classifier





Performing Background Check

- *Discriminative* approach
 - ▶ Pre-trained classifier
 - ▶ Generate background
 - ▶ Train binary classifier






Performing Background Check

- *Discriminative* approach
 - ▶ Pre-trained classifier
 - ▶ Generate background
 - ▶ Train binary classifier







Performing Background Check

- *Discriminative* approach
 - ▶ Pre-trained classifier
 - ▶ Generate background
 - ▶ Train binary classifier




Performing Background Check

- *Discriminative* approach
 - ▶ Pre-trained classifier
 - ▶ Generate background
 - ▶ Train binary classifier





Performing Background Check

- *Familiarity* approach
 - ▶ Pre-trained classifier
 - ▶ Learn $q_f(x) \in [0, 1]$
 - ▶ Use inductive bias






Performing Background Check

- *Familiarity* approach
 - ▶ Pre-trained classifier
 - ▶ Learn $q_f(x) \in [0, 1]$
 - ▶ Use inductive bias






Performing Background Check

- **Familiarity** approach
 - ▶ Pre-trained classifier
 - ▶ Learn $q_f(x) \in [0, 1]$
 - ▶ Use inductive bias







Performing Background Check

- *Familiarity* approach
 - ▶ Pre-trained classifier
 - ▶ Learn $q_f(x) \in [0, 1]$
 - ▶ Use inductive bias






Performing Background Check

- *Familiarity* approach
 - ▶ Pre-trained classifier
 - ▶ Learn $q_f(x) \in [0, 1]$
 - ▶ Use inductive bias







Performing Background Check

- *Familiarity* approach
 - ▶ Pre-trained classifier
 - ▶ Learn $q_f(x) \in [0, 1]$
 - ▶ Use inductive bias






Performing Background Check

- *Familiarity* approach
 - ▶ Pre-trained classifier
 - ▶ Learn $q_f(x) \in [0, 1]$
 - ▶ Use inductive bias







Performing Background Check

- **Familiarity** approach
 - ▶ Pre-trained classifier
 - ▶ Learn $q_f(x) \in [0, 1]$
 - ▶ Use inductive bias







Performing Background Check

- *Familiarity* approach
 - ▶ Pre-trained classifier
 - ▶ Learn $q_f(x) \in [0, 1]$
 - ▶ Use inductive bias







Performing Background Check

- *Familiarity* approach
 - ▶ Pre-trained classifier
 - ▶ Learn $q_f(x) \in [0, 1]$
 - ▶ Use inductive bias







Performing Background Check

- *Familiarity* approach
 - ▶ Pre-trained classifier
 - ▶ Learn $q_f(x) \in [0, 1]$
 - ▶ Use inductive bias







Performing Background Check

- *Familiarity* approach
 - ▶ Pre-trained classifier
 - ▶ Learn $q_f(x) \in [0, 1]$
 - ▶ Use inductive bias



Performing Background Check

- *Familiarity* approach
 - ▶ Pre-trained classifier
 - ▶ Learn $q_f(x) \in [0, 1]$
 - ▶ Use inductive bias



Results

- Empirical evaluation
 - ▶ 41 multiclass datasets
 - ▶ 20 times 5-fold cross-validation
 - ▶ Classification with confidence
 - ▶ Outlier detection
- Cautious Classification is *equivalent* to Chow's rule [Chow, 1970]

Results

- Empirical evaluation
 - ▶ 41 multiclass datasets
 - ▶ 20 times 5-fold cross-validation
 - ▶ Classification with confidence
 - *Significantly better* than [Li et al., 2014] (Wilcoxon test $p < 0.001$)
 - ▶ Outlier detection

- Cautious Classification is *equivalent* to Chow's rule [Chow, 1970]

Results

- Empirical evaluation
 - ▶ 41 multiclass datasets
 - ▶ 20 times 5-fold cross-validation
 - ▶ Classification with confidence
 - *Significantly better* than [Li et al., 2014] (Wilcoxon test $p < 0.001$)
 - ▶ Outlier detection
 - *Competitive results* with two specialized methods [Tax and Duin, 2008]
- Cautious Classification is *equivalent* to Chow's rule [Chow, 1970]

Results

- Empirical evaluation
 - ▶ 41 multiclass datasets
 - ▶ 20 times 5-fold cross-validation
 - ▶ Classification with confidence
 - *Significantly better* than [Li et al., 2014] (Wilcoxon test $p < 0.001$)
 - ▶ Outlier detection
 - *Competitive results* with two specialized methods [Tax and Duin, 2008]
- Cautious Classification is *equivalent* to Chow's rule [Chow, 1970]

Conclusion

- *General technique* to perform:
 - ▶ Cautious classification
 - ▶ Outlier detection
 - ▶ Classification with confidence
- Comparable and better results than *special purpose approaches*
- *Model agnostic*

Conclusion

- *General technique* to perform:
 - ▶ Cautious classification
 - ▶ Outlier detection
 - ▶ Classification with confidence
- Comparable and better results than *special purpose approaches*
- *Model agnostic*

Conclusion

- *General technique* to perform:
 - ▶ Cautious classification
 - ▶ Outlier detection
 - ▶ Classification with confidence
- Comparable and better results than *special purpose approaches*
- *Model agnostic*



Chow, C. (1970).

On optimum recognition error and reject tradeoff.

IEEE Transactions on Information Theory, 16(1):41–46.



Li, L., Hu, Q., Wu, X., and Yu, D. (2014).

Exploration of classification confidence in ensemble learning.

Pattern Recognition, 47(9):3120 – 3131.



Tax, D. and Duin, R. (2008).

Growing a multi-class classifier with a reject option.

Pattern Recognition Letters, 29(10):1565–1570.

Background Check: A general technique to build more reliable and versatile classifiers

Miquel Perello-Nieto^{*1}, Telmo M. Silva Filho^{*2}, Meelis Kull¹ and Peter Flach¹

* Equal contribution

¹Department of Computer Science, University of Bristol, UK

²Centro de Informatica, Universidade Federal de Pernambuco, Brazil

Email: ¹{Miquel.PerelloNieto, Meelis.Kull, Peter.Flach}@bristol.ac.uk, ²tmsf@cin.ufpe.br

December 13, 2016

